



Sher-Loxane™ 800

High-Performance Polysiloxane

Sher-Loxane™ 800 is a versatile, high-performance coating designed for long-term protection in highly corrosive environments. This advanced polysiloxane system delivers a high-gloss finish to bridges, water tanks, structural steel, and much more in just two coats, reducing total operational costs for a better bottom line.

Sher-Loxane™ 800

Made for long-term asset protection in the most aggressive service conditions, *Sher-Loxane™ 800* coating is a high-solids, high-gloss epoxy polysiloxane that delivers ease of use and cost savings, as well as enhanced aesthetics and durability.

Ease Of Use

Sher-Loxane™ 800 coating is compatible with prepared steel, primed substrates and previously coated surfaces. Users can apply the product in a variety of ways, giving them options to match application methods with working conditions.

- Simplified application via spray, brush or roller without thinning
- Long open time
- Reduced dry spray

Cost Savings

Whether applied as a single coat or in combination with a primer, *Sher-Loxane™ 800* eliminates one step of the coating system, saving applicators both time and money. A single coat of the product takes the place of an epoxy and polyurethane topcoat system, while a two-coat system of *Sher-Loxane™ 800* over a zinc primer replaces traditional three-coat systems using zinc primers, epoxies and polyurethanes. One less coat increases overall job profitability by reducing product and labor costs while enabling a faster return to service. The product's long-term durability also reduces costs by extending maintenance intervals.

- Fewer coats
- Reduced labor
- Shorter downtime

Aesthetics & Durability

The glossy, smooth finish of *Sher-Loxane™ 800* coating stands the test of time with exceptional atmospheric weathering resistance and long-term color and gloss retention. The product delivers excellent corrosion and chemical resistance that rivals that of conventional three-coat systems. It also features excellent adhesion properties and high abrasion resistance.

- High-gloss finish
- Long-term color and gloss retention
- Excellent corrosion, abrasion and chemical resistance



Recommended Uses

- Structural steel
- Architectural structures – Airports, stadiums, etc.
- Ship exteriors – Topsides and superstructures
- Tank exteriors
- Offshore platforms/oil & gas assets
- Water tank exteriors
- Piping exteriors
- Roller coasters
- Heavy equipment

Key Markets

- Marine
- Oil & gas
- Steel fabrication
- Power
- Bridge & highway
- Water & wastewater
- General industrial

The Sher-Loxane™ 800 Difference

Sher-Loxane™ 800 meets and exceeds the toughest industry standards while helping to extend product life cycles and reduce operating costs. The product's excellent resistance to corrosion, chemicals, abrasions and ultraviolet light enhance aesthetics and durability for long-term protection. Best of all, *Sher-Loxane™ 800* is backed by the value of Sherwin-Williams as your single-source supplier – offering over 4,000 distribution locations worldwide, unmatched service and specification support, and 150 years of product innovation.

- Fewer coats and labor hours
- Waste reduction over traditional zinc, epoxy and urethane systems
- Extended coating life cycle and maintenance intervals
- High-performance polysiloxane technology backed by Sherwin-Williams value and service

Sher-Loxane™ 800 Advantages

- High solids
- Meets stringent VOC regulations (<100 g/L)
- Formulated without isocyanates
- High flash point; non-combustible



A complete line of products. Market expertise. On-time distribution. What else would you expect from a world leader in protective coatings and linings?

It starts with a complete line of time-tested, high-performance products and some of the most innovative technologies in the coatings industry. But we know that it takes more than product alone to be a world leader in protective coatings and linings. And so do the customers that rely on us every day as we help them protect their business.



To learn more, visit us at
www.sherwin-williams.com/protective
or call 1-800-524-5979 to have a
representative contact you.

©2016 The Sherwin-Williams Company

Protective & Marine Coatings 09/16
SW247857